ThinkCentre® M58 Small (8910) - TopSeller (Windows 7)

Name	Type-model	Slot x bay	Processor	GHz	Cores	Memory[8]	SATA disk	SATA optical	Graphics	Monitor conn	DisplayPort dongle	Intel vPro	Win7 preload	Global Educ	Avail date
M58	8910-AQU	2x3	Pentium E5400	2.70	2	2GB	250GB[2]	DVD±RW	GMA	VGA, DP	None	None	Pro 32	None	Jan 10
☞ **M58**	8910-B4U	2x3	Pentium E5700	3.00	2	2GB	250GB	DVD±RW	GMA	VGA, DP	None	None	Pro 32	None	Oct 10
M58	8910-ARU	2x3	Core 2 Duo E7500	2.93	2	2GB	250GB	DVD±RW	GMA	VGA, DP	None	None	Pro 32	None	Jan 10
M58	8910-AUU	2x3	Core 2 Quad Q9500	2.83	4	*4GB*	320GB	DVD±RW	GMA	VGA, DP	None	None	Pro 32	None	Mar 10
M58	8910-ASU	2x3	Core 2 Duo E7500	2.93	2	*4GB*	320GB	DVD±RW	GMA	VGA, DP	None	None	Pro 64	None	Mar 10

- ***These small and medium business (SMB) models are part of the US TopSeller™ Program***
- ***These models have a 3-year limited warranty***[1]
- ***These systems are Microsoft® Office 2010 Product Key Ready (O10PKR)***

Positioning	*Mainstream enterprise stability and manageability*
Processor	**Intel® Pentium® Processor E5400** or **E5700** with **dual-core**, 800MHz system bus, and 2MB L2 cache or **Intel Core™ 2 Duo Processor E7500** with **dual-core**, 1066MHz system bus, and 3MB L2 cache or **Intel Core 2 Quad Processor Q9500** with **quad-core**, 1333MHz system bus, and 6MB L2 cache
Implementation	Processor in LGA775 socket
Memory	**2GB** or **4GB std**, 16GB max[8], **PC3-8500 1066MHz DDR3**, non-parity, dual-channel capable, four 240-pin DIMM sockets; *Italics:* standard memory in two sockets; two sockets available; *Non-italics:* standard memory in one socket; 3 sockets available
Graphics	**Intel Graphics Media Accelerator 4500 (GMA 4500)**, integrated graphics in Q45, uses main memory (up to 765MB *[2GB models]* or 1759MB *[4GB models]*), one analog VGA DB-15 connector, one DisplayPort™ connector (supports single-link DVI-D via cable 45J7915), HDCP, DirectX® 10, supports dual independent display

Small



Bay ① 5.25", 1.6" high, access, std optical
Bay ② 3.5", 1" high, no access, std disk
Bay ③ 3.5", .5" high, access, open (reader)

Slot 1: Low Profile, PCI Express 2.0 x16
Slot 2: Low Profile, 32-bit PCI 2.3

- Business black color; metal case
- 12.5" W X 14.0" D X 3.9" H
- 317mm W X 355mm D X 99mm H
- 16.5 lb (7.5 kg) in maximum configuration
- Toolless cover flips up and tilts backward on rear hinges
- Toolless disk, optical drive removal
- Toolless adapter retention
- Toolless systemboard retention
- System floor stand for vertical orientation

SATA disk	**250GB** or **320GB**, SATA 3.0Gb/s 7200 rpm, vibration dampening mounts
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in ICH10DO, RAID 0/1 support
SATA DVD±RW	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive
SATA cables	Two SATA cables (each 1-drop to device), two SATA connectors on planar
eSATA port	One external SATA (eSATA) port
Diskette drive	None
Media reader	None
Chipset	**Intel Q45 Express Chipset** (PCI Express® 2.0 x16), I/O Controller Hub 10 Digital Office [ICH10DO] (SATA 3.0Gb/s with RAID 0/1 support, PCI Express x1, ethernet MAC, PCI 2.3, USB, LPC bus), SMSC® SCH5617 Super I/O
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)
Rear ports	Six USB 2.0, serial (9-pin), ethernet (RJ-45), monitor (VGA DB-15, DisplayPort), eSATA
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports)
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)
Audio	High Definition (HD) Audio, Analog Devices AD1882 codec
Speaker	One internal speaker for business audio
Ethernet	Gigabit ethernet on planar, Intel 82567LM, Wake on LAN®, ASF2.0, DASH 1.0
Intel AMT	None
Modem	None
Security chip	Winbond® WPCT200 SafeKeeper™ Trusted Platform Module, TCG 1.2-compliant
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo
Mouse	Optical Wheel Mouse (USB connector), 400 dpi, black, Lenovo logo
Power supply	280 watts with variable speed fan, autosensing, two diagnostic LEDs

Security

- Security chip (see information on left)
- Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)
  - optional cable also locks the cover by deactivating the cover release buttons
- Power-on password
- Administrator password
- Hard disk password (user and master)
- Boot sequence control
- Boot without diskette, keyboard
- Serial port I/O control
- Individual USB port disablement

Supports ThinkVantage® technologies

GREENGUARD® certified
RoHS-compliant

Preloaded operating system[20]

- *Some:* Genuine Windows® 7 Professional 32
- *Some:* Genuine Windows 7 Professional 64

Preloaded applications[5] (all OSes; only some listed)

- Rescue and Recovery™
- Password Manager
- ThinkVantage System Update
- ThinkVantage Power Manager
- ThinkVantage Toolbox
- Lenovo Online Data Backup
- Norton™ Internet Security 2011 (30 days of virus definitions)
- Adobe® Reader®
- Adobe Flash® Player
- Microsoft Office 2010 preloaded; purchase product key to activate
- Roxio® Creator® Business Edition (DVD±RW)
- Roxio MyDVD® (DVD±RW)

Accessories

1GB PC3-8500 DDR3 UDIMM	45J5434
2GB PC3-8500 DDR3 UDIMM	45J5435
500GB SATA 3.0Gb/s Disk (7200 rpm)	43R1990
1TB SATA 3.0Gb/s Disk (7200 rpm)	45J7918
Super Multi-Burner DL DVD±RW SATA Drive	41N5620
DisplayPort to Single-link DVI-D Cable	45J7915
DisplayPort to VGA Monitor Cable	57Y4393

More accessories on O-M58 sheet

Acc Guide in pdf **lenovo.com**/accessoriesguide
Other accessories at **lenovo.com**/accessories

Limited Warranty[1]

- **3-year parts and labor**
- **International Warranty Service**[9]
- **Customer Replaceable Unit (CRU) parts only (with limited onsite service for selected parts**[3]**, 8 am - 5 pm, Mon - Fri coverage excluding holidays, next business day response time)**
- **Onsite service upgrade options (in eligible locations):**[7]
  - **3-year LOR 9x5, 4 hour response** (ThinkPlus™ part number 41C9192)
  - **3-year LOR 24x7, 4 hour response** (ThinkPlus part number 41C9193)
  - **4-year LOR 9x5, Next Business Day** (ThinkPlus part number 41C9194)
  - **4-year LOR 9x5, 4 hour response** (ThinkPlus part number 41C9195)
  - **4-year LOR 24x7, 4 hour response** (ThinkPlus part number 41C9196)
- **ThinkPlus services at lenovo.com**/thinkplus/warranty
- **Post warranty maintenance services available**
- **24 hour x 7 day**[14] **toll-free support during the warranty period**[1] **via 800-426-7378**

See footnotes for important warranty information

© Lenovo

☞ US model announced September 28, 2010; previous models on January 12 or February 23, 2010